



HP Cartucho de tinta DesignJet 728 magenta de 130 ml

Marca : HP

Código del producto: F9J66A

Nombre del producto : Cartucho de tinta DesignJet HP 728 magenta de 130 ml

Cartucho de tinta DesignJet HP 728 magenta de 130 ml

HP Cartucho de tinta DesignJet 728 magenta de 130 ml:

Ideal para equipos de diseño e ingeniería o grupos de trabajo que producen aplicaciones generales y CAD. Es fácil obtener resultados claros y nítidos. Diseñados con la impresora/impresora multifunción HP DesignJet como un sistema de impresión optimizado, las tintas originales HP pueden ayudar a reducir el tiempo de inactividad y aumentar la productividad. Elija entre tamaños de cartuchos de 40 a 300 ml para satisfacer sus necesidades.



Desempeño		Condiciones ambientales	
Compatibilidad *	Impresora HP DesignJet de la serie T730, impresora multifunción HP DesignJet de la serie T830	Intervalo de humedad relativa durante almacenaje	20 - 80%
Tecnología de impresión	Inyección de tinta térmica	Datos logísticos	
Colores de impresión	Magenta	Número de cajas de cartón por palé	84 pieza(s)
Código OEM	F9J66A	Dimensiones del palé (Ancho x Profundidad x Altura)	1016 x 1219,2 x 1501,14 mm
País de origen	Singapur	Cantidad por palé	1680 pieza(s)
Peso y dimensiones		Número de capas por palé	6 pieza(s)
Ancho	202 mm	Dimensiones de Palé (Ancho x Profundidad x Altura)	1016 x 1219,2 x 1501,1 mm (40 x 48 x 59.1")
Profundidad	129 mm	Peso de palé	458,5 kg (1010.8 libras)
Altura	40 mm	Peso del palé	458,5 kg
Peso	210 g	Cantidad por caja	20 pieza(s)
Empaquetado		Peso del envase completo	5,22 kg
Ancho del paquete	202 mm	Cantidad por paquete	1 pieza(s)
Profundidad del paquete	129 mm	Código de Sistema de Armomización (SA)	84439990
Altura del paquete	40 mm	Detalles técnicos	
Peso del paquete	250 g	Contenidos de caja	Cartucho de tinta
Condiciones ambientales		Total de huella de carbono (kg of CO2e)	0,8
Intervalo de temperatura operativa	5 - 40 °C	Indicación(es) de otros riesgos en la UE	EUH208: Contains sensitizing substance. May produce an allergic reaction
Intervalo de humedad relativa para funcionamiento	20 - 80%	Número de cartones por capa	14 pieza(s)
Intervalo de temperatura de almacenaje	-25 - 55 °C	Otras características	
		Código UNSPSC	44103105



0888793397855



888793397855



5054629937051



4058154018941

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.